VISION-EASE LENS
WORLDWIDE

PRODUCT REFERENCE GUIDE

Glass

Double Segments (available through special order)
71mm Dual D25 (White, PhotoGray Extra®)

Base Curve	True Curve (1.530)	Front Radius	50mm SAG*	Back Curve	Back Radius	CT (mm) Nominal	ET (mm) Nominal
2.00	2.00	265.000	1.182	-6.00	-88.33	8.2	13.3
4.25	4.15	127.711	2.471	-6.00	-88.33	7.5	9.9
6.25	6.20	85.484	3.738	-6.00	-88.33	6.6	6.3
7.25	7.19	73.713	4.369	-6.00	-88.33	7.8	6.1
8.25	8.17	64.871	5.011	-6.00	-88.33	9.5	6.3
10.25	10.09	52.527	6.331	-6.00	-88.33	11.7	5.3

Segment Separation Thru 20mm

Standard Separation: 13mm

	25 Seg
Minimum Separation:	12mm

Base Curve	White	PGX
2.00	+1.00 to +3.50	+1.00 to +3.50
4.25	+0.50 to +3.50	+0.50 to +3.50
6.25	+0.50 to +3.50	+0.50 to +3.50
7.25	+1.00 to +3.50	-
8.25	+1.00 to +3.50	+1.00 to +3.50
10.25	+1.00 to +3.50	+1.00 to +3.50

*Utilized for power calculation only, not for thickness calculation

Click Here for Additional Multifocal Technical Information

VISION-EASE LENS
WORLDWIDE

PRODUCT REFERENCE GUIDE

Glass

Double Segments (available through special order)
71mm Dual CFR (White, PhotoGray Extra®)

Base Curve	True Curve (1.530)	Front Radius	50mm SAG*	Back Curve	Back Radius	CT (mm) Nominal	ET (mm) Nominal
2.00	2.00	265.000	1.182	-6.00	-88.33	8.2	13.3
4.25	4.15	127.711	2.471	-6.00	-88.33	7.5	9.9
6.25	6.20	85.484	3.738	-6.00	-88.33	6.6	6.3
7.25	7.19	73.713	4.369	-6.00	-88.33	7.8	6.1
8.25	8.17	64.871	5.011	-6.00	-88.33	9.5	6.3
10.25	10.09	52.527	6.331	-6.00	-88.33	11.7	5.3

Segment Separation Thru 20mm

Standard Separation: 13mm

	22 Seg
Minimum Separation:	12mm

Base Curve	White	PGX
2.00	+1.25 to +3.50	+0.75 to +3.50
4.25	+1.25 to +3.50	+0.50 to +3.50
6.25	+1.25 to +3.50	+0.50 to +3.50
7.25	+1.00 to +3.50	-
8.25	+2.00 to +3.50	+1.00 to +3.50
10.25	+2.00 to +3.50	+1.00 to +3.50

*Utilized for power calculation only, not for thickness calculation

Click Here for Additional Multifocal Technical Information

VISION-EASE LENS
WORLDWIDE

PRODUCT REFERENCE GUIDE

Glass

Double Segments (available through special order)
71mm Dual D28 (White, PhotoGray Extra®)

Base Curve	True Curve (1.530)	Front Radius	50mm SAG*	Back Curve	Back Radius	CT (mm) Nominal	ET (mm) Nominal
2.00	2.00	265.000	1.182	-6.00	-88.33	8.2	13.3
4.25	4.15	127.711	2.471	-6.00	-88.33	7.5	9.9
6.25	6.20	85.484	3.738	-6.00	-88.33	6.6	6.3
7.25	7.19	73.713	4.369	-6.00	-88.33	7.8	6.1
8.25	8.17	64.871	5.011	-6.00	-88.33	9.5	6.3
10.25	10.09	52.527	6.331	-6.00	-88.33	11.7	5.3

Segment Separation Thru 20mm

Standard Separation: 13mm

	28 Seg
Minimum Separation:	13mm

Base Curve	White	PGX
2.00	+1.00 to +3.50	+1.00 to +3.50
4.25	+0.50 to +3.50	+0.50 to +3.50
6.25	+0.50 to +3.50	+0.50 to +3.50
7.25	+1.00 to +3.50	-
8.25	+1.00 to +3.50	+1.00 to +3.50
10.25	+1.00 to +3.50	+1.00 to +3.50

*Utilized for power calculation only, not for thickness calculation

Click Here for Additional Multifocal Technical Information

VISION-EASE LENS
WORLDWIDE

PRODUCT REFERENCE GUIDE

Glass

Double Segments (available through special order)
75mm Dual D28 (White, PhotoGray Extra®)

Base Curve	True Curve (1.530)	Front Radius	50mm SAG*	Back Curve	Back Radius	CT (mm) Nominal	ET (mm) Nominal
4.25	4.15	127.711	2.471	-6.00	-88.33	8.0	10.7
6.25	6.20	85.484	3.738	-6.00	-88.33	7.0	6.7
8.25	8.17	64.871	5.011	-6.00	-88.33	10.7	7.1

13mm Separation

Standard Separation: 13mm

	28 Seg
Minimum Separation:	13mm

Base Curve	White	PGX
4.25	+1.00 to +3.00	+1.00 to +3.00
6.25	+1.00 to +3.00	+1.00 to +3.00
8.25	-	+1.00 to +3.00

*Utilized for power calculation only, not for thickness calculation

Click Here for Additional Multifocal Technical Information

VISION-EASE LENS
WORLDWIDE

PRODUCT REFERENCE GUIDE

Glass

Double Segments (available through special order)
75mm Dual D35 (White, PhotoGray Extra®)

Base Curve	True Curve (1.530)	Front Radius	50mm SAG*	Back Curve	Back Radius	CT (mm) Nominal	ET (mm) Nominal
4.25	4.15	127.711	2.471	-6.00	-88.33	8.0	10.7
6.25	6.20	85.484	3.738	-6.00	-88.33	7.0	6.7
8.25	8.17	64.871	5.011	-6.00	-88.33	10.7	7.1

Standard Separation: 15mm

	35 Seg
Minimum Separation:	15mm

Base Curve	White	PGX
4.25	+1.00 to +3.00	+1.00 to +3.00
6.25	+1.00 to +3.00	+1.00 to +3.00
8.25	-	+1.00 to +3.00

*Utilized for power calculation only, not for thickness calculation

Click Here for Additional Multifocal Technical Information